

RFID Glass Tag



Application:

Animal Identification, Small Parts Identification, Medical Parts

Key Features

- Available anti-collision in LF and HF
- Memory storage options: from 64 bit read-only to 2048 bit read-write
- Standard form factors from as tiny as 1.25 x 7 mm to 3 x 15 mm; custom sizes available
- Embeddable in a broad spectrum of potential enclosure materials
- Unlimited resistance to water and chemical absorption
- High stability over fluctuating temperatures

Tag Spec.:

Item:	RFID Glass Tag	Material:	Glass
Frequency:	LF: 134.2kHz/125kHz HF: 13.56Mhz	Color:	Transparent
Standards:	ISO 11784, ISO 11785 (FDX-B)	Dimension:	3*15mm, 2.12*12mm, 2.12*8mm, 1.5*8mm, 1.4*8mm,1.25*7mm, or customized
Chip:	LF: EM4305, T5577, Hitag S256, FDX, HDX, HF: I CODE SLIX	IP Class:	IP67
Read Distance:	10~15cm	Vibration:	10G, 10Hz-2000Hz, 2 axes (IEC 68-2-6)
Working Temperature:	-30°C to + 80°C	Shock:	200g, 2 axes (IEC 68-2-27)

Application:



The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.